



## FACE MOUNT HANGERS

Model No.	Ga	Dimensions (in)				Fasteners		Factored Resistance			
		W	H	B	d <sub>e</sub> <sup>3</sup>	Header	Joist	D. Fir-L		S-P-F	
								Uplift	Normal	Uplift	Normal
								(K <sub>D</sub> =1.15)	(K <sub>D</sub> =1.00)	(K <sub>D</sub> =1.15)	(K <sub>D</sub> =1.00)
lbs	lbs	lbs	lbs								
kN	kN	kN	kN								
<b>DOUBLE 2x SIZES</b>											
LUS24-2	18	3½	3½	2	1½	4-16d	2-16d	835	2020	590	1425
								3.72	9.00	2.63	6.35
LUS26-2	18	3½	4½	2	4	4-16d	4-16d	2195	2705	1550	1910
								9.78	12.05	6.90	8.51
HHUS26-2	14	3¾	5½	3	3¼	14-16d	6-16d	2920	7335	2065	5185
								13.01	32.67	9.20	23.10
HGUS26-2	12	3¾	5½	4	4½	20-16d	8-16d	4385	8950	3100	6325
								19.53	39.87	13.81	28.17
LUS28-2	18	3½	7	2	4	6-16d	4-16d	2195	3630	1550	2565
								9.78	16.17	6.90	11.43
HHUS28-2	14	3¾	7½	3	6½	22-16d	8-16d	3765	8945	2665	6320
								16.77	39.84	11.87	28.15
HGUS28-2	12	3¾	7½	4	6½	36-16d	12-16d	6070	12980	4290	9175
								27.04	57.82	19.11	40.87
LUS210-2	18	3½	9	2	6	8-16d	6-16d	3285	4500	2320	3180
								14.63	20.04	10.33	14.16
HHUS210-2	14	3¾	9¾	3	8	30-16d	10-16d	5480	9860	3875	6970
								24.41	43.92	17.26	31.05
HGUS210-2	12	3¾	9¾	4	8½	46-16d	16-16d	6840	14330	4835	10350
								30.47	63.83	21.54	46.10
<b>TRIPLE 2x SIZES</b>											
HGUS26-3	12	4¼	5½	4	4½	20-16d	8-16d	4385	8950	3100	6325
								19.53	39.87	13.81	28.17
HGUS28-3	12	4¼	7½	4	6½	36-16d	12-16d	6070	12980	4290	9175
								27.04	57.82	19.11	40.87
HHUS210-3	14	4¼	9	3	7¼	30-16d	10-16d	5480	10550	3875	7455
								24.41	46.99	17.26	33.21
HGUS210-3	12	4¼	9¾	4	8½	46-16d	16-16d	6840	14645	4835	10350
								30.47	65.23	21.54	46.10
<b>QUADRUPLE 2x SIZES</b>											
HGUS26-4	12	6¼	5½	4	4½	20-16d	8-16d	4385	8950	3100	6325
								19.53	39.87	13.81	28.17
HGUS28-4	12	6¼	7½	4	6½	36-16d	12-16d	6070	12980	4290	9175
								27.04	57.82	19.11	40.87
HHUS210-4	14	6½	8½	3	7¼	30-16d	10-16d	5480	10550	3875	7455
								24.41	46.99	17.26	33.21
HGUS210-4	12	6¼	9½	4	8½	46-16d	16-16d	6840	14645	4835	10350
								30.47	65.23	21.54	46.10
HGUS212-4	12	6¼	10½	4	10½	56-16d	20-16d	7640	14995	5400	10595
								34.03	66.79	24.05	47.19
HGUS214-4	12	6¼	12½	4	11½	66-16d	22-16d	10130	16400	7160	11595
								45.12	73.05	31.89	51.65
<b>4x SIZES</b>											
LUS46	18	3¾	4¾	2	3¾	4-16d	4-16d	2195	2705	1550	1910
								9.78	12.05	6.90	8.51
HHUS46	14	3¾	5¼	3	3¼	14-16d	6-16d	2920	7335	2065	5185
								13.01	32.67	9.20	23.10
HGUS46	12	3¾	5¼	4	4½	20-16d	8-16d	4385	8950	3100	6325
								19.53	39.87	13.81	28.17
LUS48	18	3¾	6¾	2	3¾	6-16d	4-16d	2195	3630	1550	2565
								9.78	16.17	6.90	11.43
HHUS48	14	3¾	7½	3	6½	22-16d	8-16d	3765	8945	2665	6320
								16.77	39.84	11.87	28.15
HGUS48	12	3¾	7½	4	6½	36-16d	12-16d	6070	12980	4290	9175
								27.04	57.82	19.11	40.87
LUS410	18	3¾	8¾	2	5¾	8-16d	6-16d	3285	4500	2320	3180
								14.63	20.04	10.33	14.16
HGUS410	12	3¾	9	4	8½	46-16d	16-16d	6840	14645	4835	10350
								30.47	65.23	21.54	46.10
HGUS412	12	3¾	10¾	4	10½	56-16d	20-16d	7640	14995	5400	10595
								34.03	66.79	24.05	47.19
HGUS414	12	3¾	12¾	4	11½	66-16d	22-16d	10130	16400	7160	11595
								45.12	73.05	31.89	51.65




**Typical HUS26 with Reduced Heel Height**


(Truss Designer to provide fastener quantity for connecting multiple members together)



Double Shear Nailing Top View



Double Shear Nailing Side View  
Do not bend tab back



Dome Double Shear Nailing prevents tabs breaking off (available on some models)  
U.S. Patent 5,603,580

1. Factored uplift resistances have been increased 15% for wind or earthquake loading; no further increase is allowed.
2. Designer must ensure that hanger is compatible with truss when reduced heel height is used.
3. d<sub>e</sub> is the distance from the bearing seat to the top joist nail.
4. Resistances shown require a minimum 2-ply girder truss. For fastening to single ply truss request T-N10FORTRUSS05 and/or see installation notes.
5. **NAILS:** 16d = 0.162" dia. x 3½" long. See page 16-17 for other nail sizes and information.