

SCREWS

The Simpson Strong-Drive® wood screw (SDS series) has a hex washer head for easy driving with a 3/8" hex head socket and a low speed drill. The built-in reamer and type 17 tip cuts a hole to allow installation without predrilling. Predrilling may be necessary depending on the type and moisture content of wood. Use 5/32" drill bit.


Available in varying lengths from 1 1/2" to 6". All sizes available in zinc dichromate, which is not to be used with some types of pressure-treated lumber. Some sizes are available hot-dip galvanized, which is appropriate for outdoor use.

The SDS Screw Driver has a deep socket and magnetic tip to help provide a positive installation for the SDS Screws.


The Simpson Strong-Drive screw (SD model) features a needle point that ensures fast starts, a double thread shank that reduces installation time, a #2 deep Phillips drive that reduces stripping, and a wafer head with a low profile. Available in 1 1/4" length, with an electro-galvanized finish.

Titen Screws are 3/16" and 1/4" diameter masonry screws for attaching to concrete and masonry. See the Simpson Anchor Systems Catalog for full Titen Screw details.


Identification on all SDS screw heads (SDS 1/4x3 shown)



SDS 1/4x3HDG
US Patent
6,109,850




SDSD 3/8-RB
(Driver)



Titen
Hex Head

VERY IMPORTANT!
Use **ONLY** stainless steel fasteners with stainless steel connectors. Use **ONLY** HDG fasteners with ZMAX and post HDG connectors.



SD8x1.25



WARNING:
Industry studies show that hardened fasteners can experience performance problems in wet environments. Accordingly, use **Titen and SD8 screws** in dry, interior applications only.