

JOIST HANGERS


HUC *Concealed Flange Joist Hangers*

Aesthetic or end applications where the hanger flanges need to be concealed. Most models have triangle and round holes, which give high loads when filled with common nails. These heavy duty connectors are designed for structures requiring additional strength, longevity and safety factors.

FINISH: G90 galvanized.

INSTALLATION:

- Can be installed filling round holes only, or filling round holes and triangle holes for maximum values.




Typical
HUC48
Installation

Use 16d nails into the header, and 10dx1½" nails into a single joist. (10d nails into double, triple and 4x joists. 16d nails into 6x joists).

LB *Joist Hangers*

Top flange hanger for larger joist sizes.

FINISH: G90 galvanized.



Typical LB210
Installation
(use 16d nails into header and 10dx1½" nails into joists for all sizes)


LSSU *Light Sloped/Skewed U Hangers*

All models skew and slope adjustable on the job site! Attach joist or rafters to headers, sloped up or down, and skewed left or right, up to 45°.

FINISH: G90 galvanized.


INSTALLATION:

- Attach the sloped joist at both ends so the horizontal force developed by the slope is fully supported by the supporting members.



Typical LSSU28 Installation

Use 10d nails into header and 10dx1½" nails into joists for all sizes.



LSSU28 Top View


LSU *Light Sloped/Skewed U Hanger*

Skew and slope adjustable on the job site! Attach joists or rafters to headers, sloped up or down, and skewed left or right, up to 45°.

FINISH: G90 or ZMAX galvanized. Use HDG fasteners for ZMAX models.


INSTALLATION:

- Attach the sloped joist at both ends so the horizontal force developed by the slope is fully supported by the supporting members.



Typical LSU26 Installation

Use 10d nails into header and 10dx1½" nails into joist



LSU26 Top View

LOOKING FOR A PARTICULAR FINISH?

Most Simpson products are available in G90, the industry standard. Where greater corrosion protection is required, we offer the same product in ZMAX or HDG, or stainless steel. We are constantly modifying our product offering in response to our customers' needs. Contact us at (800) 999-5099 or www.strongtie.com for a current list of products offered in ZMAX, HDG or stainless steel. See pg 5 for Corrosion information.