

# TABLE OF CONTENTS

Wind Effects .....	4	Floor to Masonry/Concrete .....	22
General Information .....	8	Stud to Sill Plate .....	23
Corrosion Information .....	8-9	Sill Plate to Foundation .....	23
Coatings Available .....	9	Header to Wall Framing .....	24
Fasteners .....	10-11	Alternative Wind Uplift Restraint System .....	25
Truss/Rafter to Wood Double Top Plates .....	12	Stemwall/Crawlspace .....	26
Girder/Truss to Wall Framing .....	13	Pile/Girder to Wall .....	27
I-Joists to Wall Framing .....	14	Post/Column to Beam .....	28
I-Joists to Masonry/Concrete .....	14	Corner Post/Column to Beam .....	29
Embedded Truss/Rafter to Masonry/Concrete .....	15	Post/Column to Foundation .....	30
Post Installed Truss/Rafter to Masonry/Concrete .....	16	Roof Boundary Connection .....	31
Girder/Truss to Masonry/Concrete .....	17	Lateral Load .....	31
Truss/Rafter Hip to Wall .....	18	Holdowns .....	32
Truss/Rafter Hip to End Wall .....	18	Steel Strong-Wall® Shearwall .....	33
Truss/Rafter to Single Top Plate .....	19	Wood Strong-Wall® Shearwall .....	34
Hollow Column Uplift .....	19	Gable End to Wall Framing .....	35
Truss/Rafter to Stud .....	20	Valley Truss to Roof Framing .....	36
Top Plates to Stud .....	20	Drag Strut Connection .....	36
Stud to Band Joist .....	21	Hanger Uplift Considerations .....	37
Stud to Stud .....	21	Load Path Installation Considerations .....	38-39

## THE SIMPSON STRONG-TIE QUALITY POLICY

We help people build safer structures economically. We do this by designing, engineering and manufacturing “No Equal” structural connectors and other related products that meet or exceed our customers’ needs and expectations. Everyone is responsible for product quality and is committed to ensuring the effectiveness of the Quality Management System.



**Tom Fitzmyers**  
Chief Executive Officer



**Terry Kingsfather**  
President

## GETTING FAST TECHNICAL SUPPORT


When you call for engineering technical support, we can help you quickly if you have the following information at hand. This will help us to serve you promptly and efficiently.

- Which Simpson Strong-Tie catalog are you using?  
(See the front cover for the catalog number)
- Which Simpson Strong-Tie® product are you using?
- What is your load requirement?
- What is the carried member’s width and height?
- What is the supporting member’s width and height?
- What is the carried and supporting members’ material and application?

**Call 800-999-5099 | [www.strongtie.com](http://www.strongtie.com)**

## HOW TO USE THIS CATALOG

### • NEW PRODUCTS

New products are shown with the  symbol. There are also many new sizes within existing model series.



### EXTRA CORROSION PROTECTION

This icon identifies products that are available with additional corrosion protection (*ZMAX®*, *Hot-Dip Galvanized*, *stainless steel* or *the SDS double-barrier coating*). Other products may also be available with additional protection, contact Simpson Strong-Tie for options. The end of the product name will indicate what type of extra corrosion protection is provided (*Z = ZMAX*, *HDG = Hot-Dip Galvanized* or *SS = stainless steel*). See page 8-9 for information on corrosion, and visit our website [www.strongtie.com/info](http://www.strongtie.com/info) for more technical information on this topic.

*This catalog reflects changes in the allowable loads and configurations of some Simpson Strong-Tie Company Inc. products. This catalog is effective until December 31, 2010, and supersedes all information in earlier publications, including catalogs, brochures, fliers, technical bulletins, etc. Use this edition as a current reference. Information on allowable loads and configurations is updated periodically. After December 31, 2010, contact Simpson Strong-Tie Company Inc. for the most current product information. Allowable loads in this catalog are for the described specific applications of properly-installed products. Product modifications, improper loading, installation procedures, or deviations from recommended applications will affect connector allowable load-carrying capacities.*