

**APPLICATIONS: DECKS/DOCKS**



- Screws available for most deck materials, including composite and preservative-treated wood
- Fast, precise, and consistent fastening

Quik Drive® auto-feed screw driving systems are ideal for decks & docks because the holding power of screws prevents fastener heads from popping up above the planks and our extension enables stand-up-and-drive fastening.



PROCCS/CCS+ System

**PROCCS/CCS+ Combo System**




**Applications:** Decks/docks, subfloor, sheathing, wall plates, stair treads, fiber-cement siding

- Expanded depth settings for high-density materials
- Reversible and replaceable non-skid teeth attachment
- Uniform toenailing and countersink on slick surfaces
- Two screw driving attachments for added versatility
- Details, pgs 37 and 38



**2000SDS System**










**Applications:** Decks/docks, subfloor, drywall

- Interchangeable guide tubes for a variety of applications
- Affordable, mid-grade fastener driving system
- Easy to master, effortless to use
- Details, pg 45

**APPLICATIONS: DECKS/DOCKS**



	PROCCS/CCS+	2000SDS
<p><b>WSNTLG SERIES</b> N2000® coating pg 59</p> 	2", 2½", 3"	2", 2½", 3"
<p><b>WSNTLQ SERIES*</b> Wood-to-wood, twin thread Quik Guard® coating pg 59</p> 	1¾", 2", 2½", 3"	1¾", 2", 2½", 3"
<p><b>WSCTC SERIES</b> TufCote® coating pg 60</p> 	2½"	2½"
<p><b>DTHQ SERIES</b> Trim Head, Quik Guard coating pg 60</p> 	2", 2½", 3"	2", 2½", 3"
<p><b>COMPOSI-LOK (DCL) SERIES</b> Composite decking, colors and 305 stainless steel available pg 61</p> 	2½", 3"	2½", 3"
<p><b>SS3DSC SERIES</b> 305 and 316 stainless steel #10 buglehead pg 60</p> 	2½", 3"	2½", 3"
<p><b>SSDTH SERIES</b> 305 stainless steel, #8 trim head pg 61</p> 	2", 2½", 3"	2", 2½", 3"



**WSNTLG, WSCTC, WSNTLQ**  
Twin threads for fast driving,  
nibs for easy countersink



**Composi-Lok™**  
**Counterboring Wings and Cap Head**  
Designed to prevent fastener "spin  
out" with harder materials in cold or  
wet conditions and "mushrooming"  
of composite decking material during  
installation



**SSDTH Box Threads**  
Drive with less torque

\*See page 71 for WSNTL 2", 2½" and 3" Load Tables

For more information on Quik Drive screw coatings, see page 58.

**■** This teal arrow indicates products available with additional corrosion protection, making them suitable for use in some corrosive environments and with some preservative-treated woods. For more information on corrosion, see pages 8–9.