

# PROCCS COMPLETE CONTRACTOR SYSTEM

Now 1 System Drives 1" to 3" screws - one fastening system with 2 job specific tools

**DRYWALL, DECKS, DOCKS, SUBFLOOR, WALLPLATES, MORE**



## QDPRO300SG2

- Drive a variety of **1½" to 3"** screws with no adjustment. Fasten subflooring, stair treads, wallplates, decks, docks.
- Non-skid nibs and a nose contoured to deliver countersink even when toenailing.
- Clip-on Nibs are easily reversed to protect surfaces like fine deck materials.
- QuikLock™ slip-proof coupling for fast easy assembly and breakdown.
- Adjustable, easy grip, handle for greater comfort.
- Precise, self locking depth adjustment.
- Built-in bit wrench is always there when you need it.
- Limited Lifetime Warranty.



## QDA158G2

- Drive **1" to 1½"** drywall screws
- Engineered polymer body is both lightweight and durable
- Slim profile for driving in corners
- Precise 21 point depth adjustment delivers perfect countersink
- 90 day warranty

## Quik Drive® Specialty Fasteners

- The widest range of collated screws for AutoFeed drivers
- Free driving bits in every box of screws

## PROCCS SYSTEM INCLUDES

- QDPRO300SG2 AutoFeed Driving Unit Drives 1½" to 3" Screws
- QDA158G2 Drywall Attachment Drives 1" to 1½" Screws
- Stand-up Extension • Quiver • Tool Case
- Choice of DeWalt, Makita, or Porter Cable Screwgun

### PROCCS System with:

- DeWalt 2500rpm Screwgun, order - PROCCSD25K
- Makita 2500rpm Screwgun, order - PROCCSM25K
- Makita 3500rpm Screwgun, order - PROCCSM35K
- Makita 4500rpm Screwgun, order - PROCCSM45K
- Porter Cable 2500rpm Screwgun order - PROCCSP25K



# Quik Drive®

The Leading Auto-Feed Screw Driving System - Worldwide

U.S.A. 1.888.487.7845  
 Canada 1.800.465.1515  
 Australia (02) 9831 7700  
 Worldwide 1.615.230.8788  
[www.quikdrive.com](http://www.quikdrive.com)

## SCREWS available for the PROCCS Complete Contractor System

**WSNTL SERIES** #8 wood screw, twin thread, sharp point, countersink nibs, yellow zinc for interior use only, #3 sq. drive




- ICBO ER - 5053 - 2", 2 1/2" lengths
- Ideal for high density OSB

**PPSD11516S** #8 wood to steel screw, fine thread, #2 drill point, flat head, yellow zinc coating for interior use only, #3 sq. drive



- Designed to prevent floor material (up to 3/4") from "riding-up" the threads

**SS3DSCB SERIES** #10 stainless\* deck/dock screw, coarse thread, type 17 point, 305 stainless, #3 sq. drive




- Recommended for pressure treated lumber\*
- Type 17 point for easy, straight drive

**SSDTH SERIES** #7 stainless\* trim head deck/dock screw, sawtooth thread, sharp point, 305 stainless, #2 sq. drive




- Recommended for pressure treated lumber\*
- Sawtooth threads reduce friction for easier driving

**DCTE SERIES** multi-diameter composite lumber screw, triple zinc polymer plating, #2 sq. drive



- Eliminates "mushrooming" in composite deck lumber
- Available in 3 colors - tan, grey, red
- Multi-layer coating

**SSDC3S** stainless\* multi-diameter composite lumber screw, 305 stainless, #2 sq. drive




- Recommended for pressure treated lumber\*
- Eliminates "mushrooming" in composite deck lumber

**WSNTLG SERIES** #8 deck/dock screw, twin thread, sharp point, countersink nibs, N2000® mechanical galvanized, #3 sq. drive




- ICBO ER - 5053 - 2", 2 1/2" lengths

**DTHG SERIES** #8 trim head deck screw, coarse thread, type 17 point, countersink nibs, TufCote® corrosion protection, #2 sq. drive




- Type 17 point for easy, straight drive
- Trim head for neat appearance

**DWC SERIES** #6 drywall screw, coarse, sharp point, bugle head, gray phosphate finish for interior use only, phillips drive, drive with **QDA158**




- Drywall to wood

**DWF SERIES** #6 drywall screw, fine thread, sharp point, bugle head, gray phosphate finish for interior use only, phillips drive, drive with **QDA158**



- Drywall to light (20-24 ga.) steel

**DWFS D SERIES** #6 drywall screw, fine thread, #2 drill point, bugle head, yellow zinc coating for interior use only, phillips drive, drive with **QDA158**



- Drywall to heavy (16-18 ga.) steel

\*We recommend stainless steel screws for use in most pressure treated lumber including ACQ-C, ACQ-D, ACQ-D Carbonate, CBA-A, and CA-B. See [www.strongtie.com/info](http://www.strongtie.com/info) for additional information.

Stainless steel screws are softer by nature and have less torquing strength than many other types. Due to variations in materials and installation practices, Quik Drive® assumes no liability for breakage or damage due to breakage during or after installation.

Instruction Manual, Attachment Schematic, and Warranty Information available on our web site.

**Quik Drive**®  
The Leading Auto-Feed Screw Driving System - Worldwide

U.S.A. 1.888.487.7845  
Canada 1.800.465.1515  
Australia (02) 9831 7700  
Worldwide 1.615.230.8788  
[www.quikdrive.com](http://www.quikdrive.com)